



Specification Sheet

PS-4010

Solvent Based Paint Remover (Epoxy/Polyurethane)

PS-4010 is a viscous, high performance, solvent based paint stripper.

PS-4010 is used on aircraft primers, epoxies, polyurethanes, organic coatings, and most other paint systems.

- Non-flammable
- Neutral pH
- Safe on aluminum, cadmium, magnesium, ferrous alloys, titanium, and high strength steel.
- Contains phenol and sodium chromate.
- Works well in a wide range of temperatures.

Spray or brush undiluted **PS-4010** paint stripper onto surface. Allow at least 15 minutes for the paint to be loosened. Agitate to dislodge loosened paint, then squeegee stripper residues and paint from the surface. Plastics sheeting placed under the aircraft have been found to be useful to facilitate the collection of paint stripper residue.

Conditions Of humidity and temperature will dictate dwell time. Clean stripped surface with AC-2010 to remove all stripper residues.

If **PS-4010** accidentally contacts the skin, wash the contacted area with water for an extended time (15 minutes or longer). If further treatment is required apply an ointment or salve to replace skins oils and soothe the skin.

In case of contact with eyes, flush thoroughly with water and seek medical attention.

PS-4010 must be used with adequate ventilation, due to the high-chlorinated solvent content. When application is made on a large scale, full PPE gear consisting of rubber boots, gloves, rain gear, and facemask should be worn to minimize contact of the material with the skin.

Important:

PS-4010 is an chlorinated solvent based product and is corrosive to skin and eyes. **PS-4010** should always be used with adequate ventilation and proper safety equipment, including full face shield, rubber apron, boots, and gloves. If any skin contact occurs, flush with water for at least 15 minutes, then wash with soap and water. If eyes are exposed, flush with water and seek medical attention.

Caution:

Avoid contact with skin and eyes. Use rubber clothing and face shield. Use with adequate ventilation. In case of accidental contact with eyes, flush with plenty of water, and contact physician.

Health Precautions:

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical, environmental hazards, handling precautions, and first aid recommendations. An SDS is available on request. Avoid overexposure. Seek medical attention in case of extreme overexposure.

**For Industrial Use Only.
Keep away from children.**



Specification Sheet

Approved by or Conforms to the following specifications:

MIL-R-81294, Type I, Type II, Type IV, CL1, Remover, Paint Epoxy and Polyurethane Systems

All recommendations, statements, and technical data contained herein are based on tests Aero Clean Technologies, LLC believe to be reliable and correct. Accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. Users shall rely on their own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Aero Clean Technologies, LLC and Seller's sole responsibility shall be to replace only that portion of the product of Aero Clean Technologies, LLC which proves to be defective. Neither seller nor Aero Clean Technologies, LLC shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of Aero Clean Technologies, LLC shall not be binding upon the Aero Clean Technologies, LLC or seller.

Revision: 0002

Date: 5/7/2015